TOWIN

TYRE CATALOGUE

CETROC INTERNATIONAL CO.,LIMITED

This version applied for INDOCHINA IMEXTRA CO.,LTD; VIETNAM only

With special design and compound for only use of trailer or semi-trailer.

All these tyres in these catalogue cannot be used for lorries truck and buses.

***Thailand Facility**

General Rubber (Thailand) Co., Ltd

Add: No.7/538 Moo. 6 T, Mabyangporn, A, Pluakda eng, Rayong 21140

***Cambodia Facility**

General Tires Technology (Cambodia) Co., Ltd

Add: No.4 National Road 212km Prey Nob 180101. Preah Sihanouk, Cambodia

***China Facility & H.O.**

Jiangsu General Science Technology Co., Ltd. (China & HQ)

Add: JinGang Road. DongGang Town, Wuxi Jiangsu Province

TOWIN

PRODUCT DISPLAY

XR258

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER ON MID-LONG DISTANCE TRANSPORTATION

SIZE	PR	STANDARD RIM	LOAD INDEX	SPEED RATING	OUT SIZE OF INFLATION OF NEW TIRE		MAXLOAD		PRESSURE	TREAD DEPTH	ROAD CONDION
					SECTION WIDTH	OVERALL DIAMETER	SINGLE	DOUBLE			
12R22.5	18	9.00	152/149	K	300	1085	3550	3250	930	18.5	PAVING ROAD
13R22.5	18	9.75	154/151	K	320	1124	3750	3450	830	19.5	PAVING ROAD

*This product cannot be used for lorries truck and buses

XR310

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER ON MID-LONG DISTANCE TRANSPORTATION

SIZE	PR	STANDARD RIM	LOAD INDEX	SPEED RATING	OUT SIZE OF INFLATION OF NEW TIRE		MAXLOAD		PRESSURE	TREAD DEPTH	ROAD CONDION
					SECTION WIDTH	OVERALL DIAMETER	SINGLE	DOUBLE			
225/80R17.5	16	6.75	129/127	L	226	811	1850	1750	760	15	PAVING ROAD

*This product cannot be used for lorries truck and buses

XR728

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER
ON ROUGH ROADS TRANSPORTATION

SIZE	PR	STANDARD RIM	LOAD INDEX	SPEED RATING	OUT SIZE OF INFLATION OF NEW TIRE		MAXLOAD		PRESSURE	TREAD DEPTH	ROAD CONDION
					SECTION WIDTH	OVERALL DIAMETER	SINGLE	DOUBLE			
9.00R20	16	7.0	144/142	D	259	1030	2800	2650	900	20.5	ROUGH
10.00R20	18	7.5	149/146	D	278	1065	3250	3000	930	23.5	ROUGH
11.00R20	18	8.0	152/149	D	293	1096	3550	3250	930	24.5	ROUGH
12.00R20	18	8.5	154/151	E	315	1136	3750	3450	830	24.5	ROUGH

*This product cannot be used for lorries truck and buses

XR732

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER
ON ROUGH ROADS TRANSPORTATION

SIZE	PR	STANDARD RIM	LOAD INDEX	SPEED RATING	OUT SIZE OF INFLATION OF NEW TIRE		MAXLOAD		PRESSURE	TREAD DEPTH	ROAD CONDION
					SECTION WIDTH	OVERALL DIAMETER	SINGLE	DOUBLE			
9.00R20	16	7.0	144/142	D	259	1030	2800	2650	900	20	ROUGH
10.00R20	18	7.5	149/146	D	278	1065	3250	3000	930	23.5	ROUGH
11.00R20	18	8.0	152/149	D	293	1096	3550	3250	930	25.5	ROUGH
12.00R20	22	8.5	158/155	F	315	1136	4250	3875	970	26.5	ROUGH

*This product cannot be used for lorries truck and buses

XR898

SUITABLE ONLY TRAILER OR SEMI-TRAILER
ON MIXED ROAD TRANSPORTATION

SIZE	PR	STANDARD RIM	LOAD INDEX	SPEED RATING	OUT SIZE OF INFLATION OF NEW TIRE		MAXLOAD		PRESSURE	TREAD DEPTH	ROAD CONDION
					SECTION WIDTH	OVERALL DIAMETER	SINGLE	DOUBLE			
9.00R20	16	7.0	144/142	K	259	1030	2800	2650	900	17.5	MIXED ROAD
10.00R20	16	7.5	149/146	K	278	1065	3250	3000	930	20	MIXED ROAD
11.00R20	18	8.0	152/149	K	259	1096	3550	3250	930	20	MIXED ROAD
12.00R20	18	8.5	154/151	K	315	1136	3750	3450	830	20	MIXED ROAD

*This product cannot be used for lorries truck and buses

XR856

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER
ON MID-SHORT DISTANCE TRANSPORTATION

SIZE	PR	STANDARD RIM	LOAD INDEX	SPEED RATING	OUT SIZE OF INFLATION OF NEW TIRE		MAXLOAD		PRESSURE	TREAD DEPTH	ROAD CONDION
					SECTION WIDTH	OVERALL DIAMETER	SINGLE	DOUBLE			
11.00R20	18	8.0	152/149	K	295	1085	3550	3250	930	18.5	MIXED ROAD
12.00R20	20	8.5	156/153	K	315	1125	4000	3650	900	18.8	MIXED ROAD

*This product cannot be used for lorries truck and buses

XR515

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER
ON MID-SHORT DISTANCE TRANSPORTATION

SIZE	PR	STANDARD RIM	LOAD INDEX	SPEED RATING	OUT SIZE OF INFLATION OF NEW TIRE		MAXLOAD		PRESSURE	TREAD DEPTH	ROAD CONDION
					SECTION WIDTH	OVERALL DIAMETER	SINGLE	DOUBLE			
11.00R20	18	8.0	152/149	K	295	1085	3550	3250	930	16	MIXED ROAD
12.00R20	20	8.5	156/153	K	315	1125	4000	3650	900	16	MIXED ROAD

*This product cannot be used for lorries truck and buses

XR528

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER
ON MID-SHORT DISTANCE TRANSPORTATION

SIZE	PR	STANDARD RIM	LOAD INDEX	SPEED RATING	OUT SIZE OF INFLATION OF NEW TIRE		MAXLOAD		PRESSURE	TREAD DEPTH	ROAD CONDION
					SECTION WIDTH	OVERALL DIAMETER	SINGLE	DOUBLE			
10.00R20	18	7.5	149/146	K	278	1054	3250	3000	930	16	MIXED ROAD
11.00R20	18	8.0	152/149	K	293	1085	3550	3250	930	16.5	MIXED ROAD
12.00R20	18	8.5	154/151	K	315	1125	3750	3450	830	17	MIXED ROAD
11R22.5	16	8.25	146/143	K	279	1054	3000	2725	830	18	MIXED ROAD
12R22.5	18	9.00	152/149	K	300	1085	3550	3250	930	18.5	MIXED ROAD
13R22.5	18	9.75	154/151	K	320	1124	3750	3450	830	19.5	MIXED ROAD

*This product cannot be used for lorries truck and buses

XR638

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER
ON MID-SHORT DISTANCE TRANSPORTATION

SIZE	PR	STANDARD RIM	LOAD INDEX	SPEED RATING	OUT SIZE OF INFLATION OF NEW TIRE		MAXLOAD		PRESSURE	TREAD DEPTH	ROAD CONDION
					SECTION WIDTH	OVERALL DIAMETER	SINGLE	DOUBLE			
10.00R20	18	7.5	149/146	K	278	1065	3250	3000	930	18.5	MIXED ROAD
11.00R20	18	8.0	152/149	K	293	1096	3550	3250	930	19	MIXED ROAD
9.00R20	22	8.5	158/155	J	315	1136	4250	3875	970	20	MIXED ROAD
9.00R20	16	9.00	152/149	K	300	1096	3550	3250	930	19	MIXED ROAD

*This product cannot be used for lorries truck and buses

XR658

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER
ON MID-SHORT DISTANCE TRANSPORTATION

SIZE	PR	STANDARD RIM	LOAD INDEX	SPEED RATING	OUT SIZE OF INFLATION OF NEW TIRE		MAXLOAD		PRESSURE	TREAD DEPTH	ROAD CONDION
					SECTION WIDTH	OVERALL DIAMETER	SINGLE	DOUBLE			
11.00R20	18	8.0	152/149	K	293	1096	3550	3250	930	19	PAVING ROAD
12.00R20	18	8.5	154/151	K	315	1136	3750	3450	900	20	PAVING ROAD

*This product cannot be used for lorries truck and buses

XR666

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER
ON MID-SHORT DISTANCE TRANSPORTATION

SIZE	PR	STANDARD RIM	LOAD INDEX	SPEED RATING	OUT SIZE OF INFLATION OF NEW TIRE		MAXLOAD		PRESSURE	TREAD DEPTH	ROAD CONDION
					SECTION WIDTH	OVERALL DIAMETER	SINGLE	DOUBLE			
12.00R20	20	8.5	158/155	K	315	1136	4250	3875	970	19	PAVING ROAD

*This product cannot be used for lorries truck and buses

XR858

SUITABLE ONLY TRAILER OR SEMI-TRAILER
ON MIXED ROAD TRANSPORTATION

SIZE	PR	STANDARD RIM	LOAD INDEX	SPEED RATING	OUT SIZE OF INFLATION OF NEW TIRE		MAXLOAD		PRESSURE	TREAD DEPTH	ROAD CONDION
					SECTION WIDTH	OVERALL DIAMETER	SINGLE	DOUBLE			
9.00R20	16	7.0	144/142	K	259	1030	2800	2650	900	16.5	MIXED ROAD
10.00R20	18	7.5	149/146	G	278	1065	3250	3000	930	18.5	MIXED ROAD
11.00R20	18	8.0	152/149	G	293	1096	3550	3250	930	20	MIXED ROAD
12.00R20	18	8.5	154/151	K	315	1136	3750	3450	830	20	MIXED ROAD
12R22.5	18	9.00	152/149	K	300	1096	3550	3250	930	20.5	MIXED ROAD

*This product cannot be used for lorries truck and buses